



## MID CLEAN

### Safety Data Sheet

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product form : Clear liquid.  
Substance name : Phosphate Ester, 2-Butoxyethanol, Tetra Potassium Pyro Phosphate, Alkyl Dimethyl Benzyl Ammonium Chloride, Hydrogen Peroxide, Water  
CAS No : 1341-49-7 , 7664-38-2, 7664-39-3, 7732-18-5, 68391-01-5 CBI(Trade secret)  
Product code : MID CLEAN  
Formula : Proprietary mixture.  
Classification of the substance or mixture: Corrosive to metals, Category 1 Acute toxicity, Category 2, Oral Acute toxicity, Category 2, Inhalation Acute toxicity, Category 1, Dermal Skin corrosion, Category 1A Serious eye damage, Category 1

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture: Grease and grime remover for sterilizers

##### 1.3. Details of the supplier of the safety data sheet

Manufactured by Sunland Chemical & Research Inc.  
5447 San Fernando Road W  
Los Angeles, CA 90039 - USA  
T (818) 244-9600 F (818) 246-0478  
[customerservice@sunlandchemical.com](mailto:customerservice@sunlandchemical.com)  
<http://www.sunlandchemical.com>

##### 1.4. Emergency telephone number

Emergency number : PERS: 1-800-633-8253

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### GHS-US classification

Corr. 1 H290 Skin  
Corr. 1A H314 Eye  
Dam. 1 H318

##### 2.2. Label elements

###### GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

**WARNING!**

Hazard statements (GHS-US) :

H301 – Toxic if swallowed or inhaled.  
H290 - May be corrosive to metals

RPI MID CLEAN  
Safety Data Sheet

Precautionary statements (GHS-US) : H318 – Causes serious eye damage.  
 P260 - Do not breathe mist, spray, vapors  
 P264 - Wash exposed skin thoroughly after handling  
 P280 - Wear eye protection, face protection, protective clothing, and protective gloves  
 P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting  
 P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P363 - Wash contaminated clothing before reuse  
 P370+P378 - In case of fire: Use carbon dioxide (CO2), powder, alcohol-resistant foam for extinction  
 P390 - Absorb spillage to prevent material damage  
 P405 - Store locked up  
 P406 - Store in corrosive resistant container  
 P501 - Dispose of contents/container to comply with local, state and federal regulations

**2.3. Other hazards**

Other hazards not contributing to the classification : H402: Harmful to aquatic life.

**2.4. Unknown acute toxicity (GHS US)**

No data available

**SECTION 3: Composition/information on ingredients**

**3.1. Substances**

Substance type : Multi-constituent

Name	Product identifier	%	GHS-US classification
Water	(CAS No) 1341-49-7	64-84%	See Section 2.2
2-Butoxyethanol	111-76-2	2-5%	
Phosphate Ester	68439-45-2	2-8%	
Tetra Potassium Pyro Phosphate	7320-34-5	4-10%	
Alkyl Dimethyl Benzyl Ammonium Chloride	68391-01-5	<1%	
Hydrogen Peroxide	7722-84-1	0 – 2%	
Trade secret ( Not believed to impact the hazard profile)	CBI	7-10%	

Full text of H-phrases: see section 16

**3.2. Mixture**

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.
First-aid measures after inhalation	: Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.
First-aid measures after skin contact	: Wash immediately with lots of water (15 minutes)/shower. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital.
First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes. Do not apply neutralizing agents. Cover eyes aseptically. Take victim to an ophthalmologist.
First-aid measures after ingestion	: Rinse mouth with water. Immediately after ingestion: Give lots of water to drink. Give milk to drink. Do not induce vomiting. Do not give activated charcoal. Do not give chemical antidote. Immediately consult a doctor/medical service. Call Poison Information Center. Take the container/vomit to the doctor/hospital. Ingestion of large quantities: immediately to hospital.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Irritation of the respiratory tract. Dry/sore throat. Corrosion of the upper respiratory tract. Coughing. FOLLOWING SYMPTOMS MAY APPEAR LATER: Respiratory difficulties. Possible inflammation of the respiratory tract. Blue/grey discoloration of the skin.
Symptoms/injuries after skin contact	: White skin. May stain the skin. Caustic burns/corrosion of the skin. Slow-healing wounds.
Symptoms/injuries after eye contact	: Corrosion of the eye tissue. Permanent eye damage.
Symptoms/injuries after ingestion	: Nausea. Vomiting. Abdominal pain. Burns to the gastric/intestinal mucosa. Possible esophageal perforation. Shock.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Affection/dyscoloration of the teeth. Risk of pneumonia.

### 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : EXTINGUISHING MEDIA FOR SURROUNDING FIRES: All extinguishing media allowed. Unsuitable extinguishing media : No unsuitable extinguishing media known.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: DIRECT FIRE HAZARD. Noncombustible. INDIRECT FIRE HAZARD. Promotes combustion. Reactions involving a fire hazard: see "Reactivity Hazard".
Explosion hazard	: INDIRECT EXPLOSION HAZARD. Reactions with explosion hazards: see "Reactivity Hazard".

Reactivity  
Decomposes on exposure to temperature rise: release of toxic and corrosive gases/vapors. Violent to explosive reaction with many compounds e.g.: with (strong) reducers, with (some) bases, with organic material and with combustible materials with risk of spontaneous ignition. Reacts violently with (some) metals. Decomposes slowly on exposure to light: release of toxic and corrosive gases/vapors (nitrous vapors). Violent to explosive reaction with (some) metal powders: release of highly flammable gases/vapors (hydrogen).

### 5.3. Advice for firefighters

Firefighting instructions	: Cool tanks/drums with water spray/remove them into safety. Do not move the load if exposed to heat. Dilute toxic gases with water spray. Take account of toxic fire-fighting water. Use water moderately and if possible collect or contain it.
---------------------------	---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment	: Gas-tight suit. Corrosion-proof suit.
Emergency procedures	: Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. Corrosion-proof appliances. Keep containers closed. Wash contaminated clothes.

RPI MID CLEAN  
 Safety Data Sheet

**6.1.2. For emergency responders**

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing mist, Vapors, spray.  
 Emergency procedures : Stop leak if safe to do so. Ventilate area.

**6.2. Environmental precautions**

Prevent soil and water pollution. Prevent spreading in sewers.

**6.3. Methods and material for containment and cleaning up**

For containment : Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Plug the leak, cut off the supply. Dam up the liquid spill. Try to reduce evaporation. Dilute toxic gases/vapors with water spray. Take account of toxic/corrosive precipitation water. Hazardous reaction: measure explosive gas-air mixture. Reaction: dilute combustible gas/vapor with water curtain.  
 Methods for cleaning up : Take up liquid spill into inert absorbent material, e.g.: sand, earth, vermiculite or powdered limestone. Do not take up in combustible material such as: saw dust. Scoop absorbed substance into closing containers. See "Material-handling" for suitable container materials. Carefully collect the spill/leftovers. Spill must not return in its original container. Damaged/cooled tanks must be emptied. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

**6.4. Reference to other sections**

No additional information available

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Precautions for safe handling : Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Keep the substance free from contamination. Use corrosion-proof equipment. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Never dilute by pouring water to the acid. Always add the acid to the water. Keep away from naked flames/heat. Observe very strict hygiene - avoid contact. Keep container tightly closed. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.  
 Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

**7.2. Conditions for safe storage, including any incompatibilities**

Heat and ignition sources : KEEP SUBSTANCE AWAY FROM: heat sources.  
 Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: combustible materials. reducing agents. (strong) bases. cellulosic materials. organic materials. metal powders. water/moisture.  
 Storage area : Store in a cool area. Keep out of direct sunlight. Store in a dry area. Store in a dark area. Ventilation at floor level. Fireproof storeroom. Keep locked up. Provide for a tub to collect spills. Aboveground. Keep only in the original container. Store only in a limited quantity. Meet the legal requirements.  
 Special rules on packaging : SPECIAL REQUIREMENTS: hermetical. dry. clean. opaque. correctly labelled. meet the legal requirements. Secure fragile packaging in solid containers.  
 Packaging materials : SUITABLE MATERIAL: stainless steel. aluminum. iron. glass. MATERIAL TO AVOID: synthetic material.

**7.3. Specific end use(s)**

No additional information available

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

RPI MID-CLEAN (Estimated from constituent sources)		
USA ACGIH	ACGIH TWA (ppm)	2 ppm
USA ACGIH	ACGIH STEL (ppm)	4 ppm
USA OSHA	OSHA PEL (TWA) (mg/m3)	3 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	6 ppm

:

## 8.2. Exposure controls

Appropriate engineering controls	: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide adequate general and local exhaust ventilation.
Personal protective equipment	: Protective goggles. Protective clothing. Face shield. Gloves. Combined gas/dust mask with filter type NO/P2.



Materials for protective clothing  
Hand protection

Eye protection

Skin and body protection

Respiratory protection

: GIVE LESS RESISTANCE: polyethylene/ethylene vinyl alcohol. GIVE POOR RESISTANCE: chloroprene rubber. nitrile rubber. polyethylene. PVA. natural fibers.

: Gloves.

: Protective goggles.

: Head/neck protection. Corrosion-proof clothing.

: Gas mask with filter type B. Gas mask with filter type E. Gas mask with filter type NO. High vapor/gas concentration: self-contained respirator.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Molecular mass	: Not available
Color	: Colorless-water white. On exposure to light may turn yellow.
Odor	: Irritating/pungent odor.
Odor threshold	: Not available.
pH	:
	Unknown
pH solution	: Unknown
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: Unknown
Flash point	: Not applicable
Self ignition temperature	:
	Not applicable
Decomposition temperature	:
	No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	:
	1.040 – 1.05
Relative density of saturated gas/air mixture	:

RPI MID CLEAN  
Safety Data Sheet

---

Density	: No data available : 1040 – 1050 kg/m <sup>3</sup>
Solubility	: Water: Complete
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

---

Explosive properties	: No data available
Oxidising properties	: May intensify fire.
Explosive limits	: No data available

#### 9.2. Other information

Saturation concentration	: Unknown
VOC content	: Not applicable
Other properties	: Unknown.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Decomposes on exposure to temperature rise: release of toxic and corrosive gases/vapors.

#### 10.2. Chemical stability

Unstable on exposure to light.

#### 10.3. Possibility of hazardous reactions

May react violently with reducing agents.

#### 10.4. Conditions to avoid

Direct sunlight. Incompatible materials.

#### 10.5. Incompatible materials

Strong bases. Strong reducing agents. Organic compounds. Cyanides. Combustible materials. Aldehydes. Ammonia. Metals. Alcohols.

#### 10.6. Hazardous decomposition products

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization:	: Toxic on skin.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified

RPI MID CLEAN  
Safety Data Sheet

Aspiration hazard	:	Not classified
Symptoms/injuries after inhalation	:	Irritation of the respiratory tract. Dry/sore throat. Corrosion of the upper respiratory tract. Coughing. FOLLOWING SYMPTOMS MAY APPEAR LATER: Respiratory difficulties. Possible inflammation of the respiratory tract. Risk of lung edema. Blue/grey/white discoloration of the skin.
Symptoms/injuries after skin contact	:	White/Yellow skin. May stain the skin. Caustic burns/corrosion of the skin. Slow-healing wounds.
Symptoms/injuries after eye contact	:	Corrosion of the eye tissue. Permanent eye damage.
Symptoms/injuries after ingestion	:	Nausea. Vomiting. Abdominal pain. Burns to the gastric/intestinal mucosa. Possible esophageal perforation. Shock.
Chronic symptoms	:	ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Affection/discoloration of the teeth.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	:	Classification concerning the environment: not applicable.
Ecology - water	:	Water pollutant (surface water). Harmful to fishes. Harmful to invertebrates (Daphnia). May cause eutrophication. pH shift.

Alkaline Solution	Estimated from constituent components
LC50 fishes 1	135 mg/l (96 h; Lepomis macrochirus;)
EC50 Daphnia 1	180 mg/l (48 h; Daphnia magna; PURE SUBSTANCE)
LC50 fish 2	72 ppm (Gambusia affinis; PURE SUBSTANCE)
Threshold limit algae 1	> 19 mg/l (Algae; PURE SUBSTANCE)

### 12.2. Persistence and degradability

Alkaline Solution	
Persistence and degradability	Biodegradability: not applicable. No (test) data on mobility of the components of the mixture available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

### 12.3. Bioaccumulative potential

Alkaline Solution	
BCF fish 1	Not known
Log Pow	Not known
Bioaccumulative potential	Not known

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations	:	Remove waste in accordance with local and/or national regulations. Recycle/reuse. Remove for physico-chemical/biological treatment. Remove to an authorized dump (Class I). Treat using the best available techniques before discharge into drains or the aquatic environment.
--------------------------------	---	--

Additional information

### SECTION 14: Transport information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

#### 14.1. UN number

UN-No.(DOT) : NOT DOT REGULATED

DOT NA no.

#### 14.2. UN proper shipping name

DOT Proper Shipping Name : NOT DOT REGULATED

Department of Transportation (DOT) Hazard :

Hazard labels (DOT) :

Packing group (DOT) :



RPI MID CLEAN  
Safety Data Sheet

DOT Special Provisions (49 CFR 172.102) :

DOT Packaging Exceptions (49 CFR 173.xxx) :  
DOT Packaging Non Bulk (49 CFR 173.xxx) :  
DOT Packaging Bulk (49 CFR 173.xxx) :

**14.3. Additional information**

Other information : No supplementary information available.

State during transport (ADR-RID) : As liquid.

**Overland transport**

Packing group (ADR) :  
Class (ADR) :  
Hazard identification number (Kemler No.) :  
Classification code (ADR) :  
Danger labels (ADR) :

Orange plates :

**Transport by sea** :

DOT Vessel Stowage Location

DOT Vessel Stowage Other :

EmS-No. (1) :

EmS-No. (2) :

**Air transport**

DOT Quantity Limitations Passenger aircraft/rail :

:

**SECTION 15: Regulatory information**

**15.1. US Federal regulations**

MID CLEAN  
 Safety Data Sheet

RQ (Reportable quantity, section 304 of EPA's List of Lists) :	
SARA Section 311/312 Hazard Classes	

**15.2. International regulations**

**CANADA**

Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	

**EU-Regulations**

No additional information available

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Corr. 2A

Full text of H-phrases: see section 16

**15.2.2. National regulations**

<b>Ammonium Biflouride, Phosphoric acid, Proprietary ingredients</b>
Listed on the Canadian Ingredient Disclosure List

**15.3. US State regulations**

<b>Proprietary mixture</b>	
State or local regulations	U.S. - Pennsylvania - RTK (Right to Know) List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Massachusetts - Right To Know List

**SECTION 16: Other information**

Full text of H-phrases: see section 16:

RPI MID CLEAN  
Safety Data Sheet

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
H290	May be corrosive to metals
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

: 4 -

**HMIS III Rating**

Health : 2 Moderate – Can cause serious or permanent injury  
Flammability : 0 Minimal Hazard  
Physical : 0 Minimal Hazard  
Personal Protection : H

SDS US (GHS HazCom 2012)

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and Sunland Chemical assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.